









Rotary Packaging Machine with Screw Auger Filler

Packaging Versatility

The HSY-RP08-200AF are capable of performing filling with multiple standard bag styles, such as pouch bags and stand pouch with spout bags.

Application Versatility
The HSY-RP08-200AF are combined with screw auger system, which were engineered for industrial processing of dry material in either continuous or batching operations. The industrial screw feeders we manufacture are used in a wide range of material in the continuous or batching operations. The industrial screw feeders we manufacture are used in a wide range of material in the continuous or batching operations. handing applications, either in free-flowing such as pallets and powders, or more difficult moving such as pigments, fibers and sticky or lumped material. Machine designed to package an unlimited variety of products, suck as granules (eg. coffee granules), bakery and confectionery (eg. Biscuit, chocolates), loose tea, real meal complex product (eg. Rice, meat, vegetables) as well as pet food and non-food products.

Function Versatility

Reliable motors for all machine functions. From the filling until sealing. The accurate product dosing is performed immediately.

Film Material Versatility

The flexible machine offers heat-sealing and poly-sealing options, with freely adjustable sealing temperature according to product specification.

Easy rag

The modular machine design of HSY-RP08-200 with various up and downstream interfaces allows for easy integration of dosing devices (screw augers, weightier, cup-fillers, liquid pumps), coffee valve applicators, gas flusing, printers, abelers as well as check-weighter and metal detector.

Module ++

As part of the Highpack Packaging Technology portfolio, the modular machine design of the HSY-RP08-200AF allows an easy integration with other packaging equipment such as Counter Indexing Conveyor or case packers for secondary packaging.

Machine Design

The low machine height facilitates a compact product stream, leading to higher speed and increased efficiency and ergonomics.



Rotary Packaging Machine with Screw Auger Filler HSY-RP08-200AF

Technical Specification

Model HSY-RP08-200AF

Working Station 8 working position

Material (Structure) Stainless Steel 304

Packing Speed 10 - 60 bpm (depending on application)

Filling Range 100 - 2500 gram

Weight Accuracy +/- 1%

Power Requirement 8kw, 415V, 3PH, 22A, 50/60hz

Air Pressure 0.6-0.8MPa

Gas Consumption 48L/MIN

Bag Size Width 100 - 210mm x length 100-350mm

Packing material Laminated film / PE / PP &etcs...

Pattern (Pouch) Stand up pouch, Spouted pouch, Zipper pouch,

Fin/lap seal bag, Three side seal bag, Gusset bag

Machine Weight Packing Machine Approx. 1200kgs

Screw Auger Approx. 260kgs

Machine Dimension W 2100mm, L 4000mm, H 2800mm



Stand up pouch



Spouted up pouch



Zipper pouch



Fin/lap seal bag



Three seal bag



Gusset bag



No. 4873, Jalan Permatang Pauh, Kawasan Perindustrian Mak Mandin, 13400 Butterworth, Pulau Pinang, Malaysia. Tel: 604-324 2396 Fax:604-333 2396 Email: highpack@highpack.com.my Website: www.highpack.com.my



THAIM PACK CO., LTD.

75 M6 Lahan, Bangbuathong, Nonthaburi 11110 Thailand.
Tel: 66 2 194 1095 Fax: 66 2 194 1094 Email: thaimpack@gmail.com 🕤 Line ID:farishana